

The most powerful 4U platform for CT applications



Features

- Meets EIA RS-310C standard
- Rugged design
- Slide rail applicable
- 3 x 12 cm hot swap ball bearing fans
- 6 x 5.25" + 1 x 3.5" Drive Bays
- 560W redundant PSU
- 20 slots back-plane
- Fan fail alarm and over heat alarm

Specification

Construction

Heavy-duty steel with Ni plating

Drive bays

6 x 5.25" + 1 x 3.5" drive space

Cooling Fan / Air Filter

3 x 12 cm hot-swappable high-speed ball bearing fans

Power Supply

560W redundant power supply

Back Plane

20 slots PICMG back-plane

System Indicators

3 x fan fail LED, 1 x over heat LED

Front Panel Controls

1 x on/off switch; 1 x touch-free reset switch; 1 x alarm reset switch

Gross Weight

18 Kg

Net Weight

14.5 Kg

Dimension

428mm(W) X679mm (D) X176mm (H)

Operation Temperature

0 ~ 55 ° C

USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780
Tel:(714)368-3676 Fax:(714)368-9292
email: info@racksolution.com

Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,
Da -an District, Taipei City, 106, Taiwan
Tel: 886-2-2707-9990 Fax: 886-2-2707-7579