

### Socket 478 PICMG Card for Pentium® 4 / Celeron™ Processor with VGA / Gigabit LAN / Audio (Optional) / SATA

#### Features

Socket 478 for Intel Pentium 4/ Celeron processor, up to 3.2GHz

Intel 865 chipsets + ICH5, 533/800 MHz FSB

Chipset integrated VGA function

Support 10/100/1000 Base-TX Ethernet

Optional IP-ALC20 audio card

4 x USB2.0 ports, 2 x COM ports, 2 S-ATA ports

WatchDog timer & Hardware monitoring function



#### Specification

##### CPU

Support socket 478 Intel Pentium 4 / Celeron processor

##### Chipset

Intel 865G with ICH5

##### Bus Interface

Front Side Bus up to 800/533 MHz

##### Main Memory

Up to 2 GB DDR 400/ 333 SDRAM on 2 x 184-pin DIMM sockets

##### Onboard VGA Controller

Intel 865G chipset integrated VGA function

##### LAN Controller

Intel 82547GI Gigabit LAN, for 10/100/1000 Base-TX Ethernet

##### Audio

AC97 Audio pin-header (audio card with bracket by optional)

##### Serial ATA Interface

Two S-ATA ports, support data transfer rates USB

Onboard 4 x USB2.0 ports by pin-header  
[Multi-I/O Port](#)

Onboard Winbond 83627HF chip, support:

1 x IrDA by 5-pins pin-header

1 x Floppy port by pin-header

1 x SPP / EPP / ECP parallel port by pin-header

2 x COM ports for RS-232

##### Watchdog Timer

256 Levels software programmable

##### BIOS

Award BIOS

##### Power Requirement

+5V@4.5A, +12V@3.3A

##### Board Dimension

338 x 122 mm (L x W)

##### Operation Temperature

0 ~ 60 °C (32 ~140 °F)

#### USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780

Tel:(714)368-3676 Fax:(714)368-9292

email: info@racksolution.com

#### Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,

Da -an District, Taipei City, 106, Taiwan

Tel: 886-2-2707-9990 Fax: 886-2-2707-7579