

*2U rack mount server chassis with 4x 3.5" swapable IDE HDD carriers  
+ 1x CD-ROM + 1x FDD*



### Specification

#### Construction

Heavy Duty Cold Rolled Electroplated Steel

#### Drive bays

1 x 5.25" + 1 x 3.5" drive bays

4x 3.5" hot-swap IDE HDD carriers

#### Cooling Fan / Air Filter

4 x 8cm (42.5 CFM) Heavy Duty Ball Bearing Fans

#### Power Supply

2U 300 ATX Single PSU

#### Main Board Size

Support ATX M/B (Max. to 12" x 13")

#### System Indicator

LEDs for Power ON/OFF, HDD Active

#### Front Panel Controls

1 x power on/off switch

1 x touch-free reset switch

#### Operation Temperature

0 to 55 °C (32 to 131 °F)

#### Gross Weight

17 Kg (37.5 lb)

#### Dimension

483mm (W) x 651mm (D) x 88mm (H)

19" (W) x 25.6" (D) x 3.5" (H)

### Features

Meets EIA RS-310C standard

Heavy duty steel with Ni plating

Slide rail applicable

6-slot PICMG butterfly backplane

Replaceable air filter

2 x 8 cm high-speed ball-bearing fans for better ventilation

Lockable door

Front accessible PS/2 keyboard connector

Easy assembly and maintenance

#### USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780

Tel:(714)368-3676 Fax:(714)368-9292

email: info@racksolution.com

#### Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,

Da -an District, Taipei City, 106, Taiwan

Tel: 886-2-2707-9990 Fax: 886-2-2707-7579