

### 19 Slots (12xPCI) PICMG Back-plane

#### Features

Fit for 19 slots chassis

Support ATX and AT type power connector

2 x slots PICMG for SBC board

5 x ISA slots for full-size ISA boards

12 x PCI slots for full-size boards

Well designed sufficient power is delivered to every slot



#### Specification

##### Connector:

**PICMG:** 2 x PICMG slots for SBC board.

**ISA:** 5 x ISA slots for full-size ISA board.

##### PCI:

- 3 x 5V 32-bit PCI slots for full-size boards on the primary bus.
- Those slots are Master/Slave configurable by using Bus Mastering Scheme.
- 9 x 5V/3.3V 32-bit PCI slots for full-size boards on the secondary bus

**AT connector:** 1 x AT standard 12 pin power connector.

**ATX connector:** 1 x ATX standard 20 pin power connector.

##### ATX control connector:

- 1 x ATX control connector to distribute signals coming from the CPU board onto connector for soft on/off an ATX power supply.
- P10 power connector: 1 x P10 standard power connector.
- Pairs of header for local connection of a keyboard, fan power, and power LED.

##### PCB:

- The Printed Circuit Board's (PCB) overall dimensions are 265mm x 415mm(10.43" x 16.33"), and total thickness is 1.6mm.
- Mounting holes are provided and are located to conform to the baby AT form factor. Mounting Holes are connected to signal ground internally.

##### Standard:

- PCI-conforms to PICMG rev. 2.1 specification.
- ISA-conforms to IEEE P996 specification..

#### USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780  
Tel:(714)368-3676 Fax:(714)368-9292  
email: info@racksolution.com

#### Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,  
Da -an District, Taipei City, 106, Taiwan  
Tel: 886-2-2707-9990 Fax: 886-2-2707-7579